

Power Xpress bollards

The Power Xpress bollard provides reliable, safe EV charging in all conditions. Available as a single or double charging station bollard, the 1/4" gauge steel bollard protects your investment and is impact resistant.

Each bollard features the same fully weatherproof, adjustable output Power Xpress charging station with 23-foot cables and galvanized steel construction. Dual bollard charges 2 vehicles simultaneously at full power.



Specifications	Single Bollard	Dual Bollard		Single Bollard	Dual Bollard
Adjustable Amperage	12-32 Amps	12-32 Amps x2	Input Current	30 Amps	30 Amps x2
Voltage	96-264 VAC	96-264 VAC x2	Breaker Size	40 Amps	40 Amps x2
Cord Length	23 ft	23 ft x2	Temperature Rating	-40°F to +122°F (-40°C to +50°C)	
Weight	125 lbs	150 lbs	Enclosure	NEMA Type 4X; rain, sleet, snow, ice, cold, and heat resistant	
Dimensions	Diameter 7.2" Height 58"	Diameter 7.2" Height 68"	Input/Output Power	7.2 kW	7.2 kW x2

Power Max

The original Power Max will work with all electric vehicles in North America, providing unparalleled value and reliability. The weather-resistant housing is suitable for indoor or outdoor installations.

With 16- and 30-amp options and a cable length up to 25 feet, there is a Power Max to perfectly match your charging needs. Charge at up to 7.2 kW for larger EV batteries, reducing overall charging time compared to the factory 110V cordset.

Bosch has engineered Power Max to meet or exceed SAE J1772, NEC 625 and NEMA 3R standards. Power Max has earned cUL and UL listing with integrated safety features that protect the driver and vehicle.



Specifications

Part No.	EL-51245	EL-51253	EL-51254
Amperage	16 Amps	30 Amps	30 Amps
Voltage	208 VAC- 240 VAC	208 VAC- 240 VAC	208 VAC- 240 VAC
Cable Length	12 ft	18 ft	25 ft
Weight	11 lbs	14 lbs	17 lbs
Dimensions	16 x 14 x 5	16 x 14 x 5	16 x 14 x 5
Input/Output Power	3.3 kW	7.2 kW	7.2 kW
Enclosure	NEMA Type 3R; indoor/outdoor	NEMA Type 3R; indoor/outdoor	NEMA Type 3R; indoor/outdoor